

TOOLS & METERS





MT500

R3 295.00 WRS R3 850.00



- -50°C to 1000°C 20:1 spot ratio
- Multipoint laser
- 150ms response time Adjustable emissivity





- **Clamp Meter** ■ 33mm jaw
- 600A AC
- 1000V AC/DC -30°C to 350°C IR Temp
- 100mF Capacitance
- CAT IV 600V









- 20 pre-set wire gauge ■ -5 to 50°C Temp
- 1999.9Ω Resistance ■ 60 000 count display







Insulation Tester

- 250V-500V-1000V ■ 2000MΩ
- 1000V DC / 750V AC 1mA output current 200mA Short Circuit
- Live Circuit Warning & Buzzer
- Dual digital display CAT IV 600V

Smart Mode

continuity

25mm jaw

600A AC/DC

600V AC/DC

6000 Count

CAT III 600V

DCV, ACV, Ω &

automatically identifies

-30°C to 1000°C K-Type

R1 495.00

WRS R1 730.00

MODE MAX MIN

MT766 AC/DC TRMS CLAMP METER STHERMOMETER

000



0.00x 530v

HOLD B LOCK CONTINUOUS

SEL POWER > 25

Clamp Meter

600A AC/DC

■ 1000V AC/DC

CAT IV 600V

■ -30°C to 350°C IR Temp

■ 100mF Capacitance

RZ 995.00

WAS R3 660.00

5-In-1 Environmental

Air Temp, Humidity Lux

R4 995.00

WAS R5 995.00

K-Type Temp

& Velocity

■ 33mm jaw

AT713 SOOA AC/DC



- 125V-250V-500V-1000V ■ 4000MΩ
- CAT IV 600V 1mA output current
- 200mA short Circuit Dual Digital display with Bargraph





09 15

HOLD B LOCK CONTINUOUS ZERO







NCV

Display



MODE NAUSH O

Simultaneously

■ -10°C to 60°C

Temperature

for airflow

m/s or knots

CMM or CFM

Data Logger

20 points average

Wind speed measure

in mph, ft/min, km/h,

16 Memory locations

MT948

R4 950.00

WAS R5 790.00



MODE MAX MIN



- 600A AC/DC ■ 1000V AC/DC
- Temp, Ω, CAP & Hz -30°C to 350°C IR Temp 4:1 Spot Ratio
- CAT IV 600V MT767















Solar Clamp Meter

- 37mm jaw
- 1000A AC/DC
- 1500V DC & 1000V AC ■ -40°C to 1000°C K-Type
- TFT Colour Display Ω, CAP & Hz INRUSH Current
- Data Logging & **Trend Capture** CAT IV 600V









TOOLS &

METERS

MT390: Multifunction Tester ■ Insulation & earth resistance Continuity & RCD test Loop/PSC & phase rotation Voltage, current & Frequency

MT290: EVSE Adaptor

Single & three phase

CAT IV 400V

- Tests Mode 3 EV equipment Connection for Type 2 and Type 1
- PE Pre-Test
- Simulation of CP Error "E" and PE Error



0





MT100: Continuity and Bell Tester

 Remotely identify and label two wires using flashing remote probes

BUDDY 1

R26 500.00


- Distance 3000m (26 Gauge min) Lightweight and pocket size
- 1000V AC 60Hz
- 3-Phase Indication Built-in LED flashlight


MT401: NCV Detector

CAT IV 600V









1000V Tools & Back Pack

KV-5RRS – 5pc Ring Gear Wrench Set KV-9SS – 9pc Spanner and Socket Set VSKN011S - 50mm straight Stripping Knife

VSKN012C - 28mm curved Stripping Knife

VSKN013S – 38mm curved Stripping Knife













MT720 – 400A AC Clamp Meter

MT310 - ELCB Tester

■ MT930 - Phase Rotation Meter

MT1877 - 1000V TRMS Multimeter MTKBAG - Heavy Duty Meter Case





*From 1 October 2023 until 29 February 2024 | Ts & Cs: Promotion applies to new orders placed during the specified time period *Offer Valid While Stocks Last. Distributors Discounts Reduced. E&OE

Free Speaker or Digital Watch

with selective products

Sound Level

TOOLS & METERS

TRMS Multimeter

10mF Capacitance

-200°C to 1350°C K-Type

50000 Count TFT Display

Data Logging & Trend Capture

MT1005

R7 495.00

WRS R8 770.00

H&W Analysis Clamp Meter

33mm jaw

1000A AC/DC

CAT IV 600V

Harmonic 1-25

■ 1500V DC & 1000V AC

Data Logging & Trend Capture

Single phase - Active, Reactive,

Apparent and Power Factor

MT785

R6 995.00

WAS R8 185.00

6000µF Capacitance

1000V AC/DC

IP67, Ω & Hz

CAT IV 600V

499.8°

2023

MAJOR

496.59

NSULATION TEST

HOLD

STORE CDAR MAX MIN PLANTS PEAK

2023 TOOLS & METERS

KV7-38

R14 995.00

WRS R17 559.00

TRMS Multimeter

4000µF Capacitance

MT1881

RZ 495.00

WAS RZ 985.00

1000V AC/DC

6000 Count

CAT IV 600V

Ω & Hz

IP67

4.8 MEAS





MT390: Multifunction Tester

- Loop/PSC & phase rotation

(MATOR)

438.2

1 Men

Battery Powered

Copper 400mm² / Aluminum

Dies, 2x 4.0Ah Lithium batteries.

Rated pressure: 120kN

charger & carrying Case

Crimping Tool

Stroke: 42mm

300mm²

 Insulation & earth resistance
Voltage, current & Frequency Continuity & RCD test CAT IV 400V



- 37mm jaw 1000A AC/DC
- 1500V DC & 1000V AC
- 80x80 pixel -20°C to 260°C
- Thermal Temp -40°C to 1000°C K-Type
- INRUSH Current
- Data Logging & Trend Capture CAT IV 600V

MT784 R17 995.00



- 80 x 80 pixels
- 50Hz image resolution -20°C to 650°C
- 6400 Point Real Temp
- Hot, Cold & Centre Spot
- 3.5" TFT touch screen
- 30m Laser Distance



R31 000.00

AS R36 450.00



-

508.5

F1 F2 F3



Thermal Imaging Multimeter 1000V AC/DC

- 6mF Capacitance
- Ω & Hz ■ -20°C to 260°C
- Thermal Temp -40°C to 600°C K-Type
- 6000 count TFT display
- 80 x 80 pixel CAT IV 600V

MT2005 R17 500.00





ECT400

Battery Powered Crimping Tool

- Copper 240mm² / Aluminium 185mm² Stroke: 14mm
- Dies, 2x 2.5Ah Lithium batteries, charger

Rated pressure: 50kN

& carrying Case



Battery Powered Cable Cutter Ø85mm cutting range

- Cutting Force: 60kN Cuts Armoured Cu/Al cable, ACSR,
- Cu/Al cable
- Dies, 2x 4.0Ah Lithium batteries, charger & carrying Case



ECC85 R32 000.00 /AS R37 730.00

Insulation Tester &

- **TRMS Multimeter** ■ 50V-100V-250V-500V-1000V
- 5GΩ
- 1000V AC/DC Temp, Ω, CAP & Hz CAT IV 600V

MT565 R9 525.00 WRS R11 115.00



- **Thermal Imager** ■ 384 x 288 pixels
- 50Hz image resolution
- -20°C to 650°C 110 592 Point Real Temp
- Hot, Cold & Centre Spot
- 3.5" TFT touch screen
- 30m Laser Distance
- 8 Colour palettes





Transmitter Measurement

Detects interruptions & short

circuits in cables & concealed

electrical circuits, identifies

fuses/breakers and assigned

current circuits.

CAT III 300V



TRMS Multimeter

- 1500V DC & 1000V AC
- -50°C to 1000°C K-Type 40mF Capacitance
- Ω & Hz IP67

1000V Tool Kit

1000V AC

■ Use on live conductors up to

Conforms to IEC 60900 standards

Hz% RANGE MAX REL

IP67

SO sec. MAX A CAT IV SOOV TO CAT II 1000V

Individually tested to 10 000V

Chrome Vanadium Steel

Tarpaulin Tool Backpack

- 40000 Count
- CAT IV 600V







MT290: EVSE Adaptor

- Single & three phase Tests Mode 3 EV equipment Connection for Type 2 and
- PE Pre-Test Simulation of CP Error "E"

and PE Error







2000Ω earth resistance

- 200V earth voltage
- 1000V DC / 750V AC
- 200kΩ resistance CAT IV 600V
- MT330 R3 800.00

WRS R4 450.00 🧻



• Ω & Hz IP67



1000V AC/DC

MT1877

TRMS Multimeter

99.99mF Capacitance

R2 150.00



Manual Ranging **Multimeter** 200µF Capacitance

1000V DC & 700V AC

Laser Distance Meter

Area, volume calculations

Indirect measurement using

MT152

R3 295.00

WAS R3 845.00

Built-in spirit Level

Pythagoras

Tripod thread

Backlit Display

■ 100m

- -20°C to 760°C K-Type
- Ω & Hz
- IP67 2000 Count

CAT IV 600V MT1883 R1 880.00



Hz% RANGE MAX REL IP67 HOLD

CAT II 1000V

MA FUSED COM

RANGE REL Hz% HOLD

TRMS Multimeter

- 1500V DC & 1000V AC
- -20°C to 1000°C K-Type 100mF Capacitance
- Ω & Hz
- IP67 6000 Count
- CAT IV 600V







- **Circuit Breaker Finder**
- Automatic scanning technology
- Identifies circuit breakers & fuses Built in 30mA RCD tester Visual & audible indication









Automotive Battery

 Tests all Automotive sealed Lead Acid Batteries, AGM Flat, AGM Spiral, Gel and EFB batteries. Testing Standards CCA, BCI, CA, MCA, JIS, DIN, IEC, EN, SAE, GB





Correct wiring status Backlit display CAT IV 600V

MT350 R4 275.00 WRS R4 995.00

■ 0.1Ω to 2000Ω loop impedance





*From 1 October 2023 until 29 February 2024 | Ts & Cs: Promotion applies to new orders placed during the specified time period *Offer Valid While Stocks Last. Distributors Discounts Reduced. E&OE 086 162 5678



6 6



C SOA